



PAINT SPECIFICATIONS: ALL CAST IRON AND STEEL LIGHT POLE PARTS ARE TO BE FACTORY PRIME PAINTED WITH "TNEMEC" PRIMER AND FACTORY FINISH PAINTED WITH "TNEMEC" PEKING BLUE, ENDURASHIELD #F175B2705A 8556A, OR APPROVED EQUAL.



* TOP OF FOUNDATION TO BE LEVEL, 1" MIN HEIGHT ABOVE TOP OF SIDEWALK

TOP OF FOUNDATION DETAIL



LUMINARE POLE AND FOUNDATION DETAIL NTS

VISCO (VI-WB/21-G1-F/35'-LA/8') POLE AND BASE ASSEMBLY (7 GA, 9" BASE DIA, STEEL FLUTED TAPERED POLE 0.14"/FT TAPER) APPLY SILICONE SEALANT AT INSTALLATION VISCO WB/21 SPLIT CAST IRON BASE WITH REMOVABLE ACCESS DOOR (4) 11" SLOTS ACCEPTING: (4) 1" x 36" A307 GALVANIZED ANCHOR BOLTS 1" A36 STEEL PLATE 12" BASE PLATE DETAIL

ROADWAY LUMINARE AND POLE NTS

NOTES:

- 1. HAND HOLE ACCESS DOOR SHALL BE MOUNTED AT 270°
- 2. HAND HOLE ACCESS DOOR FOR RECEPTACLE SHALL BE MOUNTED AT 90°

CITY OF REDMOND, WASHINGTON

APPROVED BY: RON GRANT

CITY ENGINEER

REVISION DATE: MARCH 01, 2011





STANDARD DETAILS

ROADWAY LUMINAIRE AND POLE

FILE NAME: SD470.DWG DET

DETAIL NUMBER: 470